



Bridge Rectifiers

D3KB10 THRU D3KB100 100 to 1000 V 3.0 A


Typical Applications

General purpose use in AC/DC bridge full wave rectification for SMPS, lighting ballast, adapter, battery charger, home appliances, office equipment, and telecommunication applications.

Features And Mechanical Data

- Package:GBP
- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- Glass passivated Junction chip
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed 250 °C/10 seconds at terminals applications.
- Terminals: Tin plated leads, solderable per STD-002 and JESD22-B102
- Polarity: As marked on body

D3K



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified. Single phase , half wave, 60HZ, resistive or inductive load. For capacitive load, derate current by 20%.

	Symbols	D3KB10	D3KB20	D3KB40	D3KB60	D3KB80	D3KB100	Units
Maximum Recurrent Peak Reverse Voltage	VRRM	100	200	400	600	800	1000	Volts
Maximum RMS Voltage	VRMS	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	VDC	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Current. Lead Length @Ta(Fig 1)	I(AV)	3.0						Amp
Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC method) (Rating of per diode)	IFSM	80						Amp
Maximum Instantaneous Peak Forward Voltage @Drop Per Diode at 1/2 I(AV)	VF	1.0						Volts
Maximum DC reverse current at rated DC blocking voltage per	IR	5 500						uAmp
Current squared time @1ms≤t≤8.3ms TJ=25 °C , Rating of per diode	I ² t	26.6						A ² S
Typical Thermal Resistance	RθJA	55						°C/W
Operating Temperature Range	TJ	-55 to +150						°C
Storage Temperature Range	TSTG	-55 to +150						°C



Bridge Rectifiers

D3KB10 THRU D3KB100 100 to 1000 V 3.0 A




Fig. 1 Forward Derating Curve




Fig. 2 Typical Forward Characteristics




Fig. 3 Peak Forward Surge Current




FIG4: Typical Reverse Characteristics