




Schottky Barrier Rectifier

SR340 THRU SR3200 40 to 200 V 3.0A

DO-27(DO-201AD)

Features And Mechanical Data

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Metal silicon junction ,majority carrier conduction
- Guard ring for over voltage protection
- Low power loss ,high efficiency
- High current capability ,Low forward voltage drop
- High surge capability
- For use in low voltage ,high frequency inverters, free wheeling ,and polarity protection applications
- High temperature soldering:260°C MAX at 10 seconds, per JESD 22-B106 or MIL-STD-750,method 2026
- Case: JEDEC D0-27(D0-201AD) molded plastic body



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60HZ, resistive or inductive load. For capacitive load, derate current by 20%.

Type Number and marks	Symbols	SR 340	SR 345	SR 360	SR 380	SR 3100	SR 3120	SR 3150	SR 3200	Units
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	40	45	60	80	100	120	150	200	Volts
Maximum RMS Voltage	V _{RMS}	28	31.5	42	56	70	84	105	140	Volts
Maximum DC Blocking Voltage	V _{DC}	40	45	60	80	100	120	150	200	Volts
Maximum Average Forward Rectified Current. Lead Length @Ta(Fig 1)	I _(AV)	3.0								Amp
Peak Forward Surge Current, 8.3 ms single half-sine-wave superimposed on rated load (JEDEC method) (Rating of per diode)	I _{FSM}	80								Amp
Maximum instantaneous forward voltage at I _(AV)	V _F	0.55	0.70		0.85		0.90		0.95	Volts
Maximum DC reverse current at rated DC blocking voltage per T _J =25°C T _J =100°C	I _R	0.2			0.1				mA	
		20			6					
Typical Thermal Resistance	R _{θJA}	25								°C/W
Junction Temperature	T _J	-65 to +150								°C
Storage Temperature Range	T _{STG}	-65 to +150								°C

*This product The above data sheet typical data meet the Mentioned standards,designers for reference only

Ordering Information (Example)

Prefered P/N	Package code	Unit weight(g)	Minimum Package(pcs)	Inner box Quantity(pcs)	Outer carton quantity(pcs)	Delivery mode
DO-27	T1	about 1.05	1250	1250	12500	Tape
DO-201AD	B1	about 1.05	250	250	12500	Bulk
DO-201AE	B2	about 1.05	250	250	10000	Bulk



Schottky Barrier Rectifier

SR340 THRU SR3200 40 to 200 V 3.0A




Fig. 1 Forward Derating Curve




Fig. 2 Typical Forward Characteristics




Fig. 3 Peak Forward Surge Current




FIG.4-TYPICAL FORWARD CHARACTERISTICS